05.09-6

SLITTING LINE

technical details:

LIMONTA / EUROSLITTER manufacturer year of construction 1998 / 2001 / 2016 material width 40 - 750 mm material thickness 0.40 - 3.00 mmstrip width mm coil weight 8.0 t cutting speed 50 - 120 m/min working direction right ⇒ left required space (I x w) weight

line consisting of:

coil carcapacity8,0 t

decoiler
 capacity
 coil inside diameter
 coil outside diameter
 508 / 610 mm
 1.600 mm

paper recoiler

coil opener hydraulically

• pinch roll with deflector roll

• manual centering units

PVC applicator

PVC unwinder

 slitting shear knife shaft diameter

knife shaft diameter 160 mm blade diameter 250 mm blade diameter - grinded 225 mm

• scrap conveyor with hydraulic vertical movement hydraulically

• scrap winder

• rubberized pinch roll

deflector roll at loop entry

• transfer table

• brake unit

loop exit saddle

felt press

feeding pinch roll

- page 1 of 2 -

All technical data are based on suppliers information and therefore without obligation for us. The machines are subject to prior sale; this offer is subject to our General terms and Conditions.

05.09-6

=====

crop shear deflector roll feeding table

decoilercapacity10,0 t

paper decoiler

coil carcapacity8,0 t

• turnstile 4 arms
capacity each arm
10,0 t

- coil tilting unit with centering device and manual radial strapping
- stacker with mechanical clamping device
- electric control cabinets and desks
- hydraulic unit
- safety protections

• cutting performance table:

thickness mm	max. number - cuts	speed m/min.
0,40 / 0,50	18	120
0,60 / 0,70	14	110
0,08 / 1,20	10	100
1,50	9	80
1,80 / 2,00	8	50
2,50	6	50
3,00	5	50

- page 2 of 2 -

All technical data are based on suppliers information and therefore without obligation for us. The machines are subject to prior sale; this offer is subject to our General terms and Conditions.